



LHR Series-High Rate

LHR12300W(12V300W)




Specifications

Rated Voltage	12V	
Nominal Rate($W_{15}, 1.67V/cell$)	300W/cell	
Nominal Capacity($C_{10}, 1.80V/cell$)	75Ah	
Dimension	Length	256±2mm (10.1 inches)
	Width	173±2mm (6.81 inches)
	Container Height	213±2mm (8.39 inches)
	Total Height	216±2mm (8.50 inches)
Approx Weight	23.7kg (52.3 lbs)	
Terminal	T11(M8)	
Container Material	ABS: UL 94 HB or V-0	
Rated Capacity(25°C)	75.0 Ah	C10(7.50A, 1.80V/cell)
	69.8 Ah	C8(8.72A, 1.80V/cell)
	65.5 Ah	C5(13.1A, 1.75V/cell)
	58.5 Ah	C3(19.5A, 1.75V/cell)
	44.1 Ah	C1(44.1A, 1.60V/cell)
Max. Discharge Current	750A (5s)	
Internal Resistance(25°C)	Approx 5.0mΩ	
Operating Temp. Range	Discharge	-20 ~ 55°C (-4 ~ 131°F)
	Charge	-20 ~ 40°C (-4 ~ 104°F)
	Storage	-15 ~ 50°C (5 ~ 122°F)
Nominal Operating Temp. Range	25±3°C (77±5°F)	
Max.Charging Current(25°C)	18.75A	
Charge voltage(25°C)		Charge voltage Temp. Coefficient
	Float	2.25 ~ 2.30V/cell -3mV/cell/°C
	Equalization	2.30~2.40V/cell -4mV/cell/°C
Effect of temp. to Capacity	40°C (104°F)	106%
	25°C (77°F)	100%
	0°C (32°F)	86%
Self Discharge	≤3%/month @ 25°C	



Layout



Constant Current Discharge (Amperes) at 25 °C (77°F)

F.V/Time	5min	10min	15min	20min	30min	45min	1h	1.5h	2h	3h	4h	5h	8h	10h
1.85V/cell	177.6	145.4	133.5	102.3	73.5	51.6	39.4	27.1	21.7	18.2	14.4	12.6	8.35	7.22
1.80V/cell	195.4	158.2	139.8	113.9	78.6	54.5	41.6	28.7	22.9	19.0	15.2	12.9	8.72	7.50
1.75V/cell	213.1	171.0	150.0	115.3	80.3	55.9	42.7	29.4	23.5	19.5	15.5	13.1	8.90	7.63
1.70V/cell	230.9	183.8	154.8	117.6	81.8	56.7	43.3	29.8	23.8	19.7	15.6	13.2	8.99	7.70
1.67V/cell	252.2	195.8	159.6	119.9	82.0	57.1	43.6	30.0	24.0	19.8	15.7	13.2	9.02	7.74
1.60V/cell	257.5	200.1	162.1	123.2	83.3	57.7	44.1	30.3	24.3	20.0	15.8	13.3	9.09	7.80

Constant Power Discharge (Watts/cell) at 25 °C (77°F)

F.V/Time	5min	10min	15min	20min	30min	45min	1h	1.5h	2h	3h	4h	5h	8h	10h
1.85V/cell	333.9	273.3	251.0	192.3	138.2	105.4	80.5	55.4	44.3	37.2	29.5	25.7	17.1	14.8
1.80V/cell	367.3	297.4	262.8	214.1	147.8	111.5	85.1	58.6	46.9	38.9	31.1	26.5	17.8	15.3
1.75V/cell	400.7	321.5	281.9	216.8	151.0	114.3	87.2	60.0	48.0	39.8	31.6	26.8	18.2	15.6
1.70V/cell	434.1	345.6	291.0	221.1	153.8	115.9	88.5	60.9	48.7	40.4	31.9	27.0	18.4	15.7
1.67V/cell	474.1	368.1	300.0	225.4	154.2	116.7	89.1	61.3	49.0	40.6	32.1	27.1	18.4	15.8
1.60V/cell	484.2	376.2	304.7	231.6	156.6	118.0	90.1	62.0	49.6	40.9	32.3	27.2	18.6	15.9



LHR Series-High Rate

LHR12300W(12V300W)

Applications

- UPS
- Hospitals & Testing Laboratories
- Emergency Power Supply
- Banks & Financial Markets
- Industrial Process Control Facilities
- Data & Network Operation Centers


General Features

- High quality AGM separator: extend cycle life and prevent micro short circuit
- PbCaSn alloy for plate grids: less gassing, less self-discharging
- Unique vent valve design: reduce water losing and prevent air/spark going inside


Standards

- Compliance with IEC 60896 standards
- Classified as "Long Life" according to Eurobat
- CE, UL, IEC Certified
- Manufactured in Leoch@IATF16949, ISO 45001, ISO 9001 and ISO 14001 certified production facilities


Discharge Characteristics




Float Charging Characteristics



Temperature Effects in Relation to Battery Capacity



Effect of Temperature on Long Term Float Life



Sales Offices Worldwide

China Sales Office

5th Floor, Xinhua Bldg., Nanshan Blvd.,
Nanshan, Shenzhen, China. 518052
Tel: +86-755-86036060 (100 lines)
Fax: +86-755-26067269
E-mail: export@leoch.com

North America Sales Office

19751 Descartes
Foothill Ranch, CA 92610, USA
Tel: 949-588-5853
Fax: 949-588-5966
E-mail: sales@leoch.us
Http://www.leoch.us

HongKong Sales Office

Workshop C, 33/F, TML Tower, No. 3 Hoi Shing Road,
Tsuen Wan, New Territories, Hong Kong
Tel: +852 35786666
Fax: +44 1452 690125
E-mail: sales.hk@leoch.com

UK Sales Office

9B Wheatstone Court, Waterwells, Business Park,
Gloucester, GL2-2AQ, UK United Kingdom
Tel: +44(0) 1452 729428 / 1452 729696
Fax: +44 1452 690125
E-mail: Sales.Europe@leoch.com
Http://www.leoch.eu

Singapore Sales Office

No. 1 Tech Park Crescent,
Singapore 638131
Tel: +65 68636078
Fax: +65 6863 6079
Email: sales.sg@leoch.com

EMEA Sales Office

1 Deligiorgi St., 121 31 Athens,
Greece
Tel: +30 210 5760318 (2 lines)
E-mail: support_EMEA@leoch.com
Http://www.leoch.eu

Australia Sales Office

2/29 Tarlington Place, Smithfield. NSW 2164
Australia
Tel: 02 9756 0950
E-mail: sales.au@leoch.com

India Sales Office

Shed no. A-53(b), 2nd Stage of Peenya Industrial Area,
Bangalore North Taluk, Bangalore-560058, India
Tel: +91-80-23440018/23440019
Fax: +91-80-23440017
E-mail: indiasales@leoch.com



[Http://www.leoch.com](http://www.leoch.com)

© 1999-2023 LEOCH. All rights reserved.

Trademarks and logos are the property of LEOCH and its affiliates unless otherwise noted.
Subject to revisions without prior notice E&OE.

Publication No.: LB-LHR12300W-PD-EN-V1.0-202303